

Provides the fastest and easiest attachment for curtain-wall framing.



- Vertical movement up to 3" (1-1/2" up and down).
- Rapid, one-piece installation.
- Proprietary screws provide frictionless slip connection.
- Stiffened corners result in superior design values.
- Embossed fastening patterns to ensure accurate placement of fasteners.
- 14-gauge, G-90, 50 KSI steel.



Fast Clip™



Proprietary Screw



Dietrich™ Fast Clip™ deflection clips are used to attach exterior curtain-wall studs to the building structure and provide for vertical building movement independent of the cold-formed steel framing. A Dietrich™ Fast Clip™ deflection clip installs quickly with welds, screws or powder-actuated fasteners and provides adjustable standoff to ensure a plumb wall plane. Proprietary screws are provided with each clip to ensure friction-free sliding. Each clip is also embossed with fastening patterns to ensure accurate placement of fasteners.



Available for **Overnight Delivery!**



Fast Clip™ Deflection Clips

DMF Product Code	Thickness		Design Thickness		Size		Weight/Piece		Packaging*
	Gauge	Mils	Inches	(mm)	Inches	(mm)	lbs.	(kg)	Pcs./Box
FCSC	14	68	0.0713	1.81	1-1/2 x 3-1/2 x 4-1/2	38.1 x 88.9 x 114.5	0.550	0.249	25

*Includes 55 proprietary shoulder screws per box.