

## Head-of-wall, exterior curtain-wall deflection clips for vertical building movement.

- An excellent alternative to deflection track, slip-track and track-over-track.
- Fast Clip™ slip technology.
- Available in 3" and 5" widths.
- Attaches within the wall cavity.
- Proprietary screws provide frictionless slip connections.
- Embossed fastening patterns to ensure accurate placement of fasteners.
- 14-gauge, G-90, 50 KSI steel.



**FAST TOP™ CLIP**  
HEAD-OF-WALL SLIDE CLIP

The Dietrich Fast Top™ clip is used in head-of-wall deflection conditions for in-fill curtain wall assemblies to provide for vertical wall movement. These clips are used in place of or in combination with deflection track and track-over-track assemblies. They also make a positive attachment and do not require bridging or bracing for the deflection system. The Fast Top™ deflection clip attaches to the underside of structural members, concrete decks or floor assemblies. Studs must be cut less than full height to enable vertical movement up to 2-1/2" (1-1/4" up and down). Fast Top™ deflection clips quickly install with welds, screws or powder actuated fasteners. Proprietary screws ensure frictionless deflection. These clips are also embossed with fastening patterns to ensure accurate placement of fasteners.

*Patent Pending.*



### Fast Top™ Clip (FTC3 and FTC5)

| DMF Product Code | Thickness |      |                  |      | Size              |                   | Weight/Piece |       | Packaging* |
|------------------|-----------|------|------------------|------|-------------------|-------------------|--------------|-------|------------|
|                  | Gauge     | Mils | Design Thickness |      | Inches            | (mm)              | lbs.         | (kg)  | Pcs./Box   |
|                  |           |      | Inches           | (mm) |                   |                   |              |       |            |
| FTC3             | 14        | 68   | 0.0713           | 1.81 | 4 x 1-1/2 x 3-1/4 | 101 x 38.1 x 82.6 | 0.410        | 0.186 | 25         |
| FTC5             | 14        | 68   | 0.0713           | 1.81 | 4 x 1-1/2 x 4-3/4 | 101 x 38.1 x 120  | 0.610        | 0.277 | 30         |

\*Includes 110 proprietary shoulder screws per box.